

## **NOTES:**

- 1.) SEE ADDITIONAL REQUIREMENTS, STD No MVSI-132C.
- 2.) ALL TRENCHING AND BACKFILL SHALL BE DONE IN ACCORDANCE WITH SECTION 306, STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, LATEST EDITION.
- 3.) ALL TEMPORARY PAVING SHALL HAVE A MINIMUM 2" OF AC ON LOCAL STREETS AND 3" ON ALL OTHERS.
- 4.) INCREASE BEDDING UNDER PIPE FROM 4" TO 6" FOR ROCK SUBGRADES.
- 5.) USE THIS STANDARD PLAN FOR UP TO AND INCLUDING 12" DIAMETER WATER LINE WITH 36" COVER OVER PIPE.
- 6.) LANE WIDTH REQUIREMENT MAY BE REDUCED AT DISCRETION OF CITY ENGINEER.
- 7.) 1-1/2 SACK CEMENT SLURRY MAY BE USED IF USED FOR TRENCH BACKFILL.

NOT TO SCALE



RECOMMENDED: 10 13/20 DIVISION MANAGER

PUBLIC WORKS DRECTOR / DATE

CITY ENGINEER

## MORENO CITY OF

PUBLIC WORKS DEPARTMENT - CAPITAL PROJECTS DIVISION

**WATER LINE (UP TO 12" DIA)** TRENCH BACKFILL AND ROADWAY REPAIR

STANDARD PLAN

MVSI-132E-2

SHEET 5 OF 6