

- DISCHARGE FLANGED TEE.
 - (2) COMPANION FLANGE.
- PRESSURE GAUGE.

LEGEND:

- (4) PRESSURE GAUGE.
- BYPASS 2" DIA MIN.
- 6 BUTTERFLY VALVE
- FLOW SWITCH TO BE INSTALLED IN SECTION HEADER WIRED TO PUMP PANEL.
 - (8) COMPANION FLANGE.
- BUTTERFLY VALVE.
 - (10) BUTTERFLY VALVE.
- FLANGED 90 COMBINATION PRESSURE REGULATING AND NON-SLAM CHECK VALVE.
- (12) BAILEY No 400 ACP OR CLA-VAL No 91A.
- FLANGED CONCENTRIC REDUCER.
- (4) PUMP AND MOTOR.
- CONTROLLER (3 PHASE, 230 VOLT)
 - (6) CONTROLLER SUPPORT.
- SEALTITE CONDUIT
 - (18) SUPPORT LEG.
- 36" x 42" x 20" SHEET METAL ENCLOSURE FOR EXTERIOR PUMP INSTALLATION.
- (20) GALVANIZED STEEL SKID, WITH 4 9/16" HOLES.
- PRE-CAST CONCRETE PAD BY MFG.
- (2) RIGID STEEL CONDUIT TO POWER SOURCE

NOTES:

- 1) ENCLOSURE IS REQUIRED SUBJECT TO CITY APPROVAL.
- 2) CONTRACTOR TO VERIFY AVAILABLE VOLTAGE COMPATIBLE WITH MOTOR SPECIFICATIONS.

NOT TO SCALE

STANDARD PLAN

SHEET 1 OF 1

