


- ① JUMBO RECTANGULAR PLASTIC VALVE BOX WITH LOCKING LID (PER PLAN AS SPECIFIED), SHALL BE "RCV" WITH STATION NUMBERS FOR CONTROL VALVES BRANDED ON LID
- (2) PVC LATERAL LINE ANGLE PIPE TO SPECIFIED DEPTH WITH 45 DEGREE ELLS AS NECESSARY
- (3) SCH 80 PVC TOE NIPPLE ASSEMBLY (REFER TO STANDARD MVLI-544A-0)
- (4) SCH 80 PVC UNION (FIPT x FIPT)
- (5) SCH 80 PVC CLOSE NIPPLE
- (6) WATER PROOF CONNECTORS, (SEE STANDARD MVLI-545A-0)
- (7) ELECTRIC CONTROL VALVE
- (8) FINISH GRADE
- (9) PIG TAIL EXPANSION LOOP (MIN 24" LONG)
- (10) BRASS ANGLE VALVE WITH UNION
- (1) WASHED CRUSHED AGGREGATE
- (12) SCH 80 PVC NIPPLE
- (13) CONTROL & COMMON WIRES (REFER TO STANDARD MVLI-560A-0)
- (14) IRRIGATION MAIN-LINE
- (15) SCH 80 PVC S x S x S TEE
- 16) VALVE BOX EXTENSION (AS NECESSARY)

## NOTES:

- 1) INSTALL CONTROL VALVES A MINIMUM OF 12" FROM STRUCTURES OR HARDSCAPE.
- 2) INSTALL VALVES IN PLANTER BEDS WHEREVER POSSIBLE NEXT TO SIDEWALKS.
- 3) PLACE VALVE BOX PARALLEL TO STRUCTURES OR HARDSCAPE.
- 4) PLACE AGGREGATE PRIOR TO INSTALLATION OF VALVE BOX.
- 5) ATTACH VALVE IDENTIFICATION TAG WITH APPROPRIATE CONTROLLER DESIGNATION TO CONTROL WIRE.
- 6) ONLY ONE VALVE PER BOX ALLOWED.
- 7) PLACE AGGREGATE PRIOR TO INSTALLATION OF VALVE BOX.

NOT TO SCALE



RECOMMENDED:

DIVISION MANAGER

DATE

FINAL PUBLIC WORKS DIRECTOR / DATE

CITY ENGINEER

## CITY OF MORENO VALLEY

FINANCIAL & MANAGEMENT SERVICES DEPARTMENT - SPECIAL DISTRICTS DIVISION

REMOTE CONTROL VALVE

WITH UNION

STANDARD PLAN

MVLI-552A-0

SHEET 1 OF 2