

LEGEND:

- 1) STRUCTURE OR HARDSCAPE
- (2) 10" ROUND VALVE BOX WITH "QC" BRANDED ON LID
- (3) FINISH GRADE
- (4) QUICK COUPLING VALVE (PER PLAN AS SPECIFIED)
- (5) STAINLESS STEEL SCREW CLAMP MINIMUM (3) PLACES
- (6) 3/4" WASHED CRUSHED AGGREGATE BASE
- (7) SCH 80 NIPPLE 10" LONG
- (8) SCH 80 NIPPLE 12" LONG
- (9) SCH 80 (FIPT x FIPT) PVC 90 DEGREE ELL
- (10) SCH 80 PVC CLOSE NIPPLE
- 11) PRESSURE SUPPLY LINE FITTING, (LINE SIZE SCH 80 TEE S x S x T, OR 90 DEGREE ELL WITH SCH 80 REDUCER BUSHING SPIG x FIPT)
- (12) IRRIGATION MAIN-LINE
- (13) No 4 REBAR STAKE (24° LONG)

NOTES:

- 1) PLACE AGGREGATE BASE PRIOR TO INSTALLATION OF VALVE BOX.
- 2) INSTALL Q.C.V. & BOX IN PLANTERS WHEN EVER POSSIBLE, NOT IN TURF AREAS.

NOT TO SCALE



RECOMMENDED:

DIVISION MANAGER

DATE

APPROVED:

PUBLIC WORKS DIRECTOR / DATE

CITY OF MORENO VALLEY

FINANCIAL & MANAGEMENT SERVICES DEPARTMENT - SPECIAL DISTRICTS DIVISION

QUICK COUPLING VALVE

STANDARD PLAN

MVLI-554A-0

SHEET 1 OF 2