

- finish surface of mulch (3" THICK)
- (2) 10" ROUND VALVE BOX WITH SS BOLT AND WASHER. SEE NOTE BELOW
- 3 MANUAL SHUT-OFF VALVE (INS x INS)
- 4 DRIPPERLINE MANIFOLD CONNECTION
- 5) SOIL SURFACE FINISH GRADE, 3"-4" COVER OVER PIPE
- 6 3/4" GRAVEL SUMP

APPROVED:

ML. WOR

- (7) 3/4" STAINLESS STEEL WIRE MESH, TYPE 316
- 8 CONCRETE PAVER SUPPORT (3 PER BOX)

NOTE:

TOP OF VALVE BOX TO BE INSTALLED 3" ABOVE FINISH GRADE IN PLANTER AREAS, AND EVEN WITH FINISH SURFACE OF MULCH

NOT TO SCALE



RECOMMENDED:

DIVISION MANAGER

DATE

PUBLIC WORKS DIRECTOR / DATE CITY ENGINEER

7/30/19

CITY OF MORENO VALLEY

PARKS AND COMMUNITY SERVICES DEPARTMENT

MANUAL SHUT-OFF / FLUSH VALVE (FOR DRIPPERLINE) STANDARD PLAN

MVLI-574H-1

SHEET 8 OF 12